

	SCHEDE TECNICHE / TECHNICAL SPECIFICATIONS	<b>ST354</b>	Autore ASC
	<b>BOMBOM 4 RAZZE</b> <b>BOMBOM 4 STARS</b>	Rev. 01	Data 03/06/19
			Pag. 1 di 1



Caratteristiche seduta  
*Seat specifications*

- Scocca in poliuretano rigido schiumato a freddo.
- Sedile e schienale in poliuretano morbido schiumato a freddo
- *Rigid cold-foamed polyurethane shell.*
- *Soft cold-foamed polyurethane shell.*

Caratteristiche telaio  
*Frame specifications*

- Base 4 razze in acciaio inox in tubo tondo diametro 38 mm, spessore 2 mm, secondo norma UNI EN 10305-3.
- Tubo portante in acciaio inox in tubo tondo diametro 50 mm, spessore 2 mm, secondo norma UNI EN 10305-3.
- Piatto sostegno seduta, diametro 250 mm, spessore 8 mm, secondo norma UNI EN 10130, con perno saldato, diametro 28 mm.
- *4 stars base in stainless steel in round tube diameter 38 mm, thickness 2 mm, accordingly with UNI EN 10305-3 rule.*
- *Leading edge tube in stainless steel in round tube diameter 50 mm, thickness 2 mm, accordingly with UNI EN 10305-3 rule.*
- *Support seat plate, diameter 250 mm, thickness 8 mm, accordingly with UNI EN 10130 rule, with welded pin, diameter 28 mm.*

Finitura  
*Finishing*

- Telaio cromato con spessore medio 5  $\mu$ .
- Telaio verniciato con polveri epossipoliestere spessore medio 50  $\mu$ .
- *Chrome plating with medium thickness 5  $\mu$ .*
- *Painted frame with epoxy-polyester powder with average thickness of 50  $\mu$ .*

